



# DATA SHEET

**Filter media**  
Torit-TEX™

## Torit-TEX™

<b>Product code</b>	9032
<b>Appearance</b>	White, uncorrugated
<b>Use</b>	Pleatable filter media
<b>Composition</b>	Spunbond polyester with ePTFE membrane
<b>Area weight</b> (DIN 53884)	260 g/m <sup>2</sup>
<b>Thickness</b> (DIN 53885)	0.6 mm
<b>Air Permeability</b> (DIN 53887)	35–60 l/dm <sup>2</sup> /min @ 200Pa
<b>Surface finish</b>	Tetratex® Extreme ePTFE membrane
<b>Surface electrical resistance</b> (DIN 54345)	N/A
<b>IFA/BIA certificate</b> (DIN 660335-2-69)	Class M Test report number: 201825590/6210
<b>Temperature (dry heat)</b>	
Continuous	120 °C
<b>Chemical resistance</b>	
Hydrolysis	N/A
Acids	Good
Alkalis	Good
Oxidising agents	Good
Organic solvents	Good
<b>Abrasion resistance</b>	Excellent
<b>Supports combustion</b>	Yes
<b>Application field</b>	Wide pleat spacing and smooth, hydrophobic PTFE membrane provides excellent particle release. Highly recommended for chemical, food and industrial processing, when product contamination must be minimised. Excellent performance on moist, hygroscopic or agglomerative dust.